



KTLC-17NA1/B (black) or KTLC-17NA1 (beige)

17" LCD Touch Monitor (KEYTEC Magic Touch + NEC AccuSync) Specifications:

Monitor Description: NEC Model AccuSync ASLCD72VX-BK (black) ASLCD72VX (beige)			
<i>Enjoy the latest LCD technology without the hefty price tag with the 17" NEC AccuSync LCD72VX, a value-driven flat-panel monitor. This model features Ambix® digital/analog connectivity, touch-integration capabilities, NaViSet™ software, exceptional screen performance, low power consumption and Rapid Response™ technology for virtually uninterrupted, undistorted viewing of high-speed, full-motion video.</i>			
Monitor Specifications		Touch Screen specifications	
Size	17"	Technology	Resistive
View Area	17"	Material	Plastic on Glass
Display Type	Color TFT	Surface Treatment	Anti-glare hard coating
Brightness (cd/m2)	250	Spacer	Invisible (patented)
Contrast Ratio	600:1	Light Transmission	80% nominal
Horizontal Viewing Angle	170 degrees	Scratch Resistance	3H pencil hardness min.
Vertical Viewing Angle	170 degrees	Touch Resolution	USB: 4096 x 4096 Serial: 2048 x 2048
Video Signal	Analog (DVI-D, VGA)	Interface Controller	External box, USB or Com port.
Horizontal Scan	31.5-81 KHz	Controller Size (mm)	76.2 x 38.1 x 19
Vertical Scan	56-76Hz	Power	5 VDC direct from computer.
Max. Resolution (PC)	1280 x 1024	Operating Systems	Windows 95, 98, NT, ME, 2000, XP, Vista, Mac, Linux.
VESA Mounting Holes	100 x 100 mm	Drivers	Mouse emulation (click/drag)
Response Time	5 ms	Activation Force	50-120 grams per square cm
Display Area (mm)	337.9x 270.3	Response Time	< 10 ms
Colors	16.7M	Position Accuracy	3 mm maximum error
Power (VAC)	100-240V, 50-60Hz	Touch Mode	Mouse click/drag functions
Power Consumption	30W maximum	Operating Temperature	-10 to 70 degrees C
Operating Temperature	5 to 35 degrees C	Storage Temperature	-30 to 85 degrees C
Storage Temperature	-10 to 60 degrees C	Humidity	95%RH @ 40C for 96 hours
Speakers	No	Chemical Resistance	Resist to all cleaning chemicals
USB hub	No	Durability	3 million touches each point
Dimensions (mm) WxHxD	375.4 x 326.5 x 61 without stand		
Weight (KGs)	4.2 without stand		