


Magic Touch Add-On Kit KTMT-1214



X1 = 13" (330.2 mm), Y1 = 9.5" (241.3 mm), X2 = 11.25" (285.75 mm), Y2 = 8.5" (215.9 mm).
Thickness = 0.275" (7 mm).



Add-on touch screen for 12-14" notebook computer.



USB-XD controller for USB port interface. Black or beige color.



ProE-X controller for serial port interface. Black or beige color.



6-foot (180 cm) cable attached to touch screen. Extension cable available.

Part Number	Port Required	Color	Included Drivers
KTMT-1214-USB	USB	Black	Windows 98, ME, 2000, XP, Vista, Linux.
KTMT-1214-ProE	Com1 or Com2	Black	Windows 95, NT4.0, 98, ME, 2000, XP, Vista, Linux.
KTMT-1214-USB-M	USB	Black	Mac OS 9-10. Free download Windows/Linux drivers.
Accessories Included	Driver CD, User's Manual, Stylus, Cleaning Cloth, Warranty Card.		
Warranty	Touch Screen Panel: 1-year parts/labor plus 2 more years labor only. Controller: 3-year parts/labor.		
Support	Life-time free technical support and driver upgrade.		

SPECIFICATION:

TECHNOLOGY	Resistive analog touch screen.
SPACER	Invisible spacer - patented technology
LIGHT TRANSMISSION	80% nominal
SCRATCH RESISTANCE	3H pencil hardness.
TOUCH RESOLUTION	4096 x 4096 (USB-XD) or 2048 X 2048 (ProE-X)
INTERFACE CONTROLLER	External controllers: PC - USB port or serial port. Apple - USB port.
OPERATING SYSTEMS	Windows 95, 98, ME, 2000, XP, NT4.0., Linux, Apple OS 8 to 10.
DRIVER	Mouse emulation driver.
ACTIVATION FORCE	50-120 grams per square centimeter.
RESPONSE TIME	10 msec maximum.
POSITION ACCURACY	3 mm maximum error.
TOUCH MODE	Mouse click, double click, drag, right click.
OPERATING TEMPERATURE	-10 to 70 degrees C.
STORAGE TEMPERATURE	-30 to 85 degrees C.
HUMIDITY	Pass 40 degrees C, 95% RH for 96 hours.
CHEMICAL RESISTANCE	Excellent to alcohol, acetone, grease, and general household detergent.
DURABILITY	3,000,000 touches per point minimum.